

# VacTest

## Digital Transmitter Pirani – Hot Cathode DPH 400



The Digital Transmitter DPH 400 is the latest generation of micro-controller-based vacuum gauges combining an ionization sensor after the Bayard-Alpert principle with a robust spiral coil filament Pirani to provide a full range pressure measurement from atmosphere to  $5 \cdot 10^{-10}$  mbar.

- Fully customizable parameters
- Optional display version (DPH 400 D)
- 0–10 V signal and RS485 interface
- Bayard-Alpert with double filaments for extended lifetime and high reliability
- Automatic control of the ionization sensor
- Bake-out up to 180°C without electronics removal
- 2 setpoint relays as standard
- Plug and play sensor replacement



VacTest DPH 400

VacTest DPH 400 D

Technical data		DPH 400, DPH 400 D
Measurement principle		Pirani / Bayard-Alpert
Materials exposed to vacuum		Stainless steel 1.4307, Ni, W, Pt, Yttrium coated Iridium, glass
Number of filaments		1 (Pirani) / 2 (Bayard-Alpert)
Filament material		Tungsten (Pirani) / Yttrium coated Iridium (Bayard-Alpert)
Measurement range	mbar	$1000-5 \cdot 10^{-10}$
Overpressure limit	bar abs.	4
Measurement uncertainty	% of reading	< 30% (1000–10 mbar)
		< 10% ( $10-1 \cdot 10^{-8}$ mbar)
Repeatability of measurement	% of reading	$\pm 2\%$ ( $10-1 \cdot 10^{-2}$ mbar)
		$\pm 5\%$ ( $1 \cdot 10^{-2}-1 \cdot 10^{-8}$ mbar)
Leakage rate	mbar·l/s	< $5 \cdot 10^{-10}$
Reaction time	ms	< 50
Serial interface		RS485
Electrical connection		D-Sub, 15 poles, male
Supply voltage	V	20–30
Max. power consumption	W	9/0.8 (relays / display)
Output signal		0–10 V, RS485
Setpoint relay		2 dry contacts
Relay contact rating		2A, 50VAC / 2A, 30VDC, max. 60 VA
Operating temperature	°C	+5...+60
Max. bake-out temperature	°C	180
Approximate weight	g	475
Dimensions (L x W x H)	mm	45 x 66 x 141
Vacuum connection		DN 40 ISO-KF / DN 25 ISO-KF

Vacuum gauges	Part number
DPH 400, DN 25 ISO-KF	0656202940
DPH 400, DN 40 ISO-KF	0656202942
DPH 400 D, with display, DN 25 ISO-KF	0656202941
DPH 400 D, with display, DN 40 ISO-KF	0656202943

Spare parts	Part number
Spare sensor, DN 25 ISO-KF	0680204600
Spare sensor, DN 40 ISO-KF	0680204601

Controllers	Part number
Active Sensor Controller CTR 002, 2 channels	0656202928
Active Sensor Controller CTR 004, 4 channels	0656202929

Connection	Part number
Connecting cable 2 x D-Sub 15 poles, 2 m	0671204577
Connecting cable 2 x D-Sub 15 poles, 6 m	0671204578
Connecting cable 2 x D-Sub 15 poles, 10 m	0671204580
Connecting cable 2 x D-Sub 15 poles, 20 m	0671204581
RS485 Interface converter to Bluetooth	0680204592
RS485 Interface converter to USB	0671204593
Power supply 100–240 VAC / 50–60Hz, with EU/US/UK/AUS plugs	0671204594

Software	Part number
VacTest explorer, Pro version	0870203191

For the entire product range please refer to the corresponding leaflets.

### Busch LLC

516 Viking Drive | Virginia Beach, VA 23452 | Phone 757-463-7800 | info@buschusa.com | www.buschusa.com

Argentina Australia Austria Bangladesh Belgium Brazil Canada Chile China Colombia Czech Republic Denmark Finland France Germany Hungary India Ireland Israel Italy Japan Korea Malaysia Mexico Netherlands New Zealand Norway Peru Poland Portugal Romania Russia Singapore South Africa Spain Sweden Switzerland Taiwan Thailand Turkey United Arab Emirates United Kingdom USA

Technical data is subject to change. Created in Germany. MG SPAL VACTESTDPH400 USen 06/2018 8BA